



3933 X-type

X-type 3933 is a T5 luminaire with direct and indirect symmetric light distribution for pendant installation.

The new generation X-type is a series of multi functional luminaires with excellent light output and good design features. X-type comes in a number of different versions, and can be equipped with different infill modules, sensors and LED emergency lights.



Double parabolic louvre in Miro5™ aluminum or microprismatic optic in conjunction with high efficiency reflectors. The luminaire housings are made from steel finished in white, grey or black with end caps in cast aluminum.

Supplied with 2.5m connection cord and 1m quickly adjustable wire suspension.

Also available for continuous installation. Supplied as standard with HF ballast. Also available as HF dimmable, with sensor systems and with LED emergency light.



RELATED PRODUCTS



X-type
3938

X-type
3934

X-type
3937

X-type
3936

3933 X-type

OPTIONS

X-TYPE DOUBLE PARABOLIC LOUVRE

Article No	Socket	Ilcos	Watt	Length	Width	Height	Weight	CC	IP Rating	Colours
3933-128-45	G5	FDH	1x28	1246	158	60	4.0	1200	20	□ ■ ▒
3933-135-45	G5	FDH	1x35	1546	158	60	5.0	1500	20	□ ■ ▒
3933-149-45	G5	FDH	1x49	1546	158	60	5.0	1500	20	□ ■ ▒
3933-154-45	G5	FDH	1x54	1246	158	60	4.0	1200	20	□ ■ ▒
3933-228-45	G5	FDH	2x28	1246	158	60	4.0	1200	20	□ ■ ▒
3933-235-45	G5	FDH	2x35	1546	158	60	5.0	1500	20	□ ■ ▒
3933-249-45	G5	FDH	2x49	1546	158	60	5.0	1500	20	□ ■ ▒
3933-254-45	G5	FDH	2x54	1246	158	60	4.0	1200	20	□ ■ ▒

X-TYPE MICROPRISMATIC OPTIC

Article No	Socket	Ilcos	Watt	Length	Width	Height	Weight	CC	IP Rating	Colours
3933-128-8	G5	FDH	1x28	1246	158	60	4.0	1200	20	□ ■ ▒
3933-135-8	G5	FDH	1x35	1546	158	60	5.0	1500	20	□ ■ ▒
3933-149-8	G5	FDH	1x49	1546	158	60	5.0	1500	20	□ ■ ▒
3933-154-8	G5	FDH	1x54	1246	158	60	4.0	1200	20	□ ■ ▒
3933-228-8	G5	FDH	2x28	1246	158	60	4.0	1200	20	□ ■ ▒
3933-235-8	G5	FDH	2x35	1546	158	60	5.0	1500	20	□ ■ ▒
3933-249-8	G5	FDH	2x49	1546	158	60	5.0	1500	20	□ ■ ▒
3933-254-8	G5	FDH	2x54	1246	158	60	4.0	1200	20	□ ■ ▒

ACCESSORIES

- HF dimmable
- Pull Switch
- Integrated LED emergency light unit
- Infill Module, 300mm
- Infill Module, 600mm
- Infill Module, 900mm
- Infill module LED, 300 mm
- Infill module LED, 600 mm
- Infill module LED, 900 mm
- Joint bracket
- Presence/daylight sensor dim
- Presence/daylight sensor on/off
- Bracket and 1m wire

DESIGNATION

- DA, DID, DALI, DEI, DEE
- DRBR
- EM LED
- IM 300
- IM 600
- IM 900
- IM LED 300
- IM LED 600
- IM LED 900
- JB
- SMD
- SMS
- WB

COLOURS

- Black
- Silver grey
- White

DESIGNATION

- B
- SG
- W

